



# GHS SAFETY DATA SHEET

## Weld-On® 182 Plastic Roof-Flashing Cement

Date Revised: DEC 2012

Supersedes: APR 2008

### SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** Weld-On® 182 Plastic Roof-Flashing Cement

**PRODUCT USE:** Plastic Roof-Flashing Cement

**SUPPLIER:**

**MANUFACTURER:** IPS Corporation  
17109 South Main Street, Gardena, CA 90248-3127  
P.O. Box 379, Gardena, CA 90247-0379  
Tel. 1-310-898-3300

**EMERGENCY:** Transportation: CHEMTEL Tel. 800.255-3924, 813-248-0585 (International) **Medical:** Tel. 800.451.8346, 760.602.8703 3E Company (International)

### SECTION 2 - HAZARDS IDENTIFICATION

#### GHS CLASSIFICATION:

	Health	Environmental	Physical
Acute Toxicity:	Not Classified	None Known	None Known
Skin Irritation:	Category 3	None Known	
Skin Sensitization:	NO		
Eye:	Category 2		
Aspiration Hazard :	Category 1		

**GHS LABEL:**



OR



**Signal Word:**  
Danger

**WHMIS CLASSIFICATION:** None

#### Hazard Statements

H304: May be fatal if swallowed and enters airways  
H316: Causes mild skin irritation  
H302: Harmful if swallowed  
H320: Causes eye irritation

#### Precautionary Statements

P280: Wear protective gloves/protective clothing/eye protection/face protection  
P301+310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
P331: Do NOT induce vomiting  
P501: Dispose of contents/container in accordance with local regulation

### SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

	CAS#	EINECS #	REACH Pre-registration Number	CONCENTRATION % by Weight
Petroleum Distillate (contains no asbestos fiber)	64742-88-7	265-191-7		23 - 37

All of the constituents of this adhesive product are listed on the TSCA inventory of chemical substances maintained by the US EPA, or are exempt from that listing.  
\* Indicates this chemical is subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 (40CFR372).  
# indicates that this chemical is found on Proposition 65's List of chemicals known to the State of California to cause cancer or reproductive toxicity.

### SECTION 4 - FIRST AID MEASURES

**Contact with eyes:** Flush eyes with plenty of water for 15 minutes. Get medical attention if irritation develops or persists.  
**Skin contact:** Wash exposed area with mild soap and water. Get medical attention if irritation develops or persists.  
**Inhalation:** Fresh air should alleviate any respiratory discomfort. If breathing difficulties develop or persist, get medical attention.  
**Ingestion:** Do not induce vomiting. Danger from aspirating into lungs exceeds short term toxic effects. Get immediate medical help.

### SECTION 5 - FIREFIGHTING MEASURES

**Suitable Extinguishing Media:** Water Fog, CO2 Foam, Dry Chemical  
**Unsuitable Extinguishing Media:** Water in a straight hose stream may cause fire to spread and should be used as a cooling medium only  
**Exposure Hazards:** Mists or sprays could ignite at temperatures below the indicated flash point.  
**Combustion Products:** Oxides of carbon  
**Protection for Firefighters:** Self-contained breathing apparatus or full-face positive pressure airline masks.

	Health	Flammability	Reactivity	PPE	HMIS	NFPA	0-Minimal
	2	3	1	B	2	3	1-Slight
						1	2-Moderate
							3-Serious
							4-Severe

### SECTION 6 - ACCIDENTAL RELEASE MEASURES

**Personal precautions:** Extinguish possible sources of ignition and ventilate spill area. Dike area to contain spill. Provide sufficient ventilation, use explosion-proof exhaust ventilation equipment or wear suitable respiratory protective equipment. Prevent contact with skin or eyes (see section 8).  
**Environmental Precautions:** Do not flush into sewers or natural waterways. Non-essential personnel should not enter area due to slipping hazards.  
**Methods for Cleaning up:** Clean up by absorbing on an inert absorbent or other convenient means.  
**Materials not to be used for clean up:** Aluminum or plastic containers

### SECTION 7 - HANDLING AND STORAGE

**Handling:** Avoid prolonged or repeated contact with skin and/or breathing of vapors when handling. Keep containers closed when not in use. Do not eat; drink or smoke while handling.  
**Storage:** Store in a cool, dry ventilated area away from excessive heat, sparks and open flames. Do not store with oxidizing agents. Follow all precautionary information on container label, product bulletins and literature.

### SECTION 8 - PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

EXPOSURE LIMITS:	Component	ACGIH TLV	ACGIH STEL	OSHA PEL	OSHA STEL:
	Petroleum Distillate	N/E	N/E	N/E	N/E

**Engineering Controls:** Use local exhaust or dilution ventilation as appropriate to control vapor or mist to below permissible exposure limits  
**Monitoring:** Maintain breathing zone airborne concentrations below exposure limits.  
**Personal Protective Equipment (PPE):**  
**Eye Protection:** Chemical safety goggles with splash shields.  
**Skin Protection:** Neoprene rubber or other chemical resistant material. Use chemical resistant boots, apron, etc. as necessary to prevent contamination of clothing and skin contact.  
**Respiratory Protection:** Use NIOSH/MSHA approved respirators when vapors or mist concentration exceed permissible exposure limits.



# GHS SAFETY DATA SHEET

Weld-On® 182 Plastic Roof-Flashing Cement

Date Revised: DEC 2012

Supersedes: APR 2008

## SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b>	Black paste	<b>Odor Threshold:</b>	Not Available
<b>Odor:</b>	Petroleum Odor		
<b>pH:</b>	Not Applicable		
<b>Melting/Freezing Point:</b>	Not Available		
<b>Boiling Point:</b>	300 - 400 °C (150 - 206 °F)	<b>Evaporation Rate:</b>	< 1.0 (BUAC = 1)
<b>Flash Point:</b>	11 °C (51 °F)	<b>Flammability:</b>	N/A
<b>Specific Gravity:</b>	1.08 @23 °C (73 °F)	<b>Flammability Limits:</b>	<b>LEL:</b> N/A
<b>Solubility:</b>	Insoluble		<b>UEL:</b> N/A
<b>Partition Coefficient n-octanol/water:</b>	Not Available	<b>Vapor Pressure:</b>	5 mm Hg @ 20 °C (68 °F)
<b>Auto-ignition Temperature:</b>	Not Available	<b>Vapor Density:</b>	> 1.0 (Air = 1)
<b>Decomposition Temperature:</b>	Not Available	<b>Other Data: Viscosity:</b>	Not Available
<b>VOC Content:</b>	Not Available		

## SECTION 10 - STABILITY AND REACTIVITY

**Stability:** Stable

**Hazardous decomposition products:** None in normal use. When forced to burn, this product gives off oxides of carbon.

**Conditions to avoid:** Exposure to excessive heat, open flames and sparks. Avoid conditions that favor the formation of excessive mists and/or fumes.

**Incompatible Materials:** Avoid strong oxidizing materials.

## SECTION 11 - TOXICOLOGICAL INFORMATION

**Likely Routes of Exposure:** Inhalation and Ingestion

### Acute symptoms and effects:

**Inhalation:** Moderate respiratory discomfort and or/or minor headaches. Toxic systemic effect.

**Eye Contact:** No significant effect beyond minor irritation are expected.

**Skin Contact:** Moderate irritation and discomfort, defatting of skin and redness are possible. Toxic systemic effects from absorption are expected to be minor.

**Ingestion:** Gastrointestinal tract irritation and/or discomfort is possible.

**Chronic (long-term) effects:** None Known

<b>Toxicity:</b>	<b>LD50</b>	<b>LC50</b>	<b>STOT</b>
Petroleum Distillate	> 5000 mg/kg (rat)	> 5500 ppm (4 hr, rat)	Not Available

<u>Reproductive Effects</u>	<u>Teratogenicity</u>	<u>Mutagenicity</u>	<u>Embryotoxicity</u>	<u>Sensitization to Product</u>	<u>Synergistic Products</u>
Not Established	Not Established	Not Established	Not Established	Not Established	Not Established

## SECTION 12 - ECOLOGICAL INFORMATION

**Ecotoxicity:** None Known

**Mobility:** In normal use, minimal emission of volatile organic compounds (VOC's) to the air takes place.

**Degradability:** Moderately biodegradable

**Bioaccumulation:** Not Available

## SECTION 13 - WASTE DISPOSAL CONSIDERATIONS

Follow local and national regulations. Consult disposal expert.

## SECTION 14 - TRANSPORT INFORMATION

**Proper Shipping Name:** Not Regulated

**Hazard Class:** NA

**Secondary Risk:** NA

**Identification Number:** NA

**Packing Group:** NA

**Label Required:** NA

**Marine Pollutant:** NA

## SECTION 15 - REGULATORY INFORMATION

**Precautionary Label Information:** Irritant

**Symbols:** Xn

**Risk Phrases:** R36/37/38: Irritating to eyes, respiratory system and skin. R65: Harmful: may cause lung damage if swallowed.

**Safety Phrases:** S2: Keep out of the reach of children  
S23: Do not breathe vapour or mist  
S24: Avoid contact with skin.  
S62: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

**Ingredient Listings:** USA TSCA, Europe EINECS, Canada DSL, Australia AICS, Korea ECL/TCCL, Japan MITI (ENCS)

## SECTION 16 - OTHER INFORMATION

**Specification Information:**

**Department issuing data sheet:** IPS, Safety Health & Environmental Affairs

**E-mail address:** <EHSinfo@ipscorp.com>

**Training necessary:** Yes, training in practices and procedures contained in product literature.

**Reissue date / reason for reissue:** 1/2/2013 / Updated GHS Standard Format

**Intended Use of Product:** Plastic Roof-Flashing Cement

All ingredients are compliant with the requirements of the European Directive on RoHS (Restriction of Hazardous Substances).

This product is intended for use by skilled individuals at their own risk. The information contained herein is based on data considered accurate based on current state of knowledge and experience. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof.